

Pana 21:9 Displays

Pana 105 Touch
Pana 105 Non-Touch

Pana 81 Touch
Pana 81 Non-Touch



Pana 21:9 Displays

- **21:9 in native 5K resolution**
- **Touch and Non-Touch versions**
- **Preloaded with SimpleShare®**

See the World through a 21:9 Lens

Pana's 21:9 ultra-wide 5K resolution brings a refreshing form factor to the conventional display market. Our 8-foot wide Pana 105 canvas optimizes team productivity allowing for improved interaction and work place collaboration.

The market most receptive to this format are enterprise and industrial companies leaning into visualization technology to be their focal point and center piece. CIOs are telling us 21:9 is making the biggest impressions enabling them to stand out, land new clients and attract better talent. That's a win-win.

Lightweight and maneuverable, the Pana is ideal for retrofits as all sizes fit into a commercial service elevator and can be mounted using standard industry hardware without reinforced concrete or steel backing. Pana's lower infrastructure costs equates to a lower cost of ownership as a result of easy retrofit, reduced energy consumption and affordable price point. All Pana displays are Energy Star certified.

PANA FEATURES

21:9 Panoramic

The extra wide form factor is inspired by our natural human ability to see wider than we see taller.

5K Resolution

Pana provides 33% more pixels with 5K resolution giving the user more real estate in which to work.

Touch User Experience

Touch enables the expectation for interactive autonomy, speed and ease-of-use. Pana interactive displays are touch driven by multiple, simultaneous collaborators.

Built for Human Interaction

More pertinent information gets placed in our visual sweet spot increasing our comprehension and productivity. And all the pixels are placed where everyone on the team can reach them preserving our dignity among our peers of not having to overreach or bend over to interact with the display.

Interactivity through SimpleShare®

Jupiter's proprietary SimpleShare software enables intuitive interaction optimized for Pana displays. The platform provides quick and easy access to your daily workflow.

Pana 21:9 Displays Specifications

| | Pana 105 Touch | Pana 105 Non-Touch | Pana 81 Touch | Pana 81 Non-Touch |
|-----------------------|---|---|--|---|
| SPECIFICATIONS | | | | |
| Resolution | 5120 x 2160 | 5120 x 2160 | 5120 x 2160 | 5120 x 2160 |
| Orientation | Landscape | Landscape and Portrait | Landscape and Portrait | Landscape and Portrait |
| Screen Size | 105" (2667 mm) diagonal | 105" (2667 mm) diagonal | 81" (2057 mm) diagonal | 81" (2057 mm) diagonal |
| Backlight Technology | DLED with local dimming | DLED with local dimming | DLED with local dimming | DLED with local dimming |
| Contrast Ratio | 1800:1 | 1800:1 | 1800:1 | 1800:1 |
| Brightness | 450 cd/m ² | 600 cd/m ² | 450 cd/m ² | 600 cd/m ² |
| Refresh Rate | 60Hz | 60Hz | 60Hz | 60Hz |
| Viewing Angle | 178° H/V | 178° H/V | 178° H/V | 178° H/V |
| Lifetime | ≥ 50,000 Hrs | ≥ 50,000 Hrs | ≥ 50,000 Hrs | ≥ 50,000 Hrs |
| Response Time | 8 ms | 8 ms | 8 ms | 8 ms |
| Display | 21:9 aspect ratio, anti-glare, IPS LCD, direct-bonding IR with 20 simultaneous touch points | 21:9 aspect ratio, anti-glare, IPS LCD | 21:9 aspect ratio, anti-glare, IPS LCD, bezel-less metal-mesh capacitive with 20 simultaneous touch points | 21:9 aspect ratio, anti-glare, IPS LCD |
| Stylus | Optional | N/A | Optional | N/A |
| OPS Slot | Yes | No | Yes | Yes |
| POWER | | | | |
| Input Current | 6A | 6A | 6A | 6A |
| Power Standby | ≥ 0.5 W | ≥ 0.5 W | ≥ 0.5 W | ≥ 0.5 W |
| Speaker Output | 2 x 16 W | 2 x 16 W | 2 x 15 W | 2 x 15 W |
| Avg Power Consumption | 140 W | 140 W | 140 W | 140 W |
| Max Power Consumption | 600 W | 600 W | 500 W | 500 W |
| USB-C PD Output | 65W | 65W | 65W | 65W |
| Operating Temperature | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) | 32°F - 104°F (0°C - 40°C) |
| CONNECTIVITY | | | | |
| DisplayPort 1.4 In | 1 | 1 | 1 | 1 |
| DisplayPort 1.4 Out | 1 | 1 | 1 | 1 |
| HDMI In | 2 | 1 | 2 | 1 |
| USB-C with 65w | 1 | 1 | 1 | 1 |
| USB 2.0 Type-A | 4 | 4 | 4 | 4 |
| 3.5mm Line Out | 1 | 1 | 1 | 1 |
| S/PDIF Optical Fiber | 1 | 1 | 1 | 1 |
| 100M Ethernet | 1 | 1 | 1 | 1 |
| RS232 / RJ45 | 1 | 1 | 1 | 1 |
| DIMENSIONS | | | | |
| Dimensions | 99.2" x 43.5" x 4.3" (2520mm x 1105mm x 109mm) | 96.5" x 40.7" x 3.7" (2450mm x 1034mm x 94mm) | 76.1" x 33.3" x 3.4" (1933mm x 846mm x 86mm) | 75.6" x 32.7" x 3.3" (1919mm x 830mm x 83mm) |
| Weight | 209.4 lbs (95 kg) | 136.7 lbs (62 kg) | | 77.2 lbs (35 kg) |
| Shipping Dimensions | 109.4" x 59" x 13" (2780mm x 1500mm x 330mm) | 105.5" x 55.1" x 12.6" (2680mm x 1400mm x 320mm) | | |
| Shipping Weight | 275.6 lbs (125 kg) | 187.4 lbs (85 kg) | | |
| VESA Mount Dimensions | 1500 mm x 500 mm | 1500 mm x 500 mm | 800 mm x 400 mm | 800 mm x 400 mm |
| Power Cable | 9.8 ft (3m) | 9.8 ft (3m) | 9.8 ft (3m) | 9.8 ft (3m) |
| CERTIFICATIONS | | | | |
| International | UL (US & Canada), CB, CE, FCC, CA65, Energy Star, RoHS | | | |



Pana 105 shown in Portrait and Landscape orientations.



jupiter.com

© 2021 Jupiter. Jupiter is a registered trademark of Jupiter Systems, Inc. Product specifications and designs are subject to change without notice. All brand and product names and logos are registered trademarks of Jupiter Systems, Inc.