

# SRET215S-10

DATA SHEET

RET S Line



## RET S Line · Retractable Motorized Monitor

State-of-the-art Retractable Motorized Monitors with slim design and slightest expression of coverplate.



# SRET215S-10

## SOLTEC TECHNICAL SPECIFICATIONS

### RETRACTABLE MOTORIZED MONITOR RET S Line

#### GENERAL DESCRIPTION

Retractable Motorized 21.5" TFT monitor for boardroom and meeting room tables with **slim design of 20mm** and automatic **20° tilt**. High-end anodized aluminium monitor and **slightest expression of coverplate**. Built-in protective glass with black border serigraphy.

The monitor has de minimal effect on boardroom table mechanization.

RS-232 serial control through DB9 connector.  
RS-485/422 serial control through In/Out RJ45 connector allowing loop and addressing.

Full range of options available.



#### DISPLAY

Panel Technology	Edge LED Technology
Display Area (mm)	476.64(H) x 268.11(V)
Size	21,5"
Pixel Pitch (mm)	0.248 x 0.248
Screen Aspect	16:9
Native Resolution	1.920 x 1.080
Viewing Angle UDLR	89°/89°/89°/89°
Contrast Ratio	5000:1 (Typ)
Brightness cd/m2	300 (Typ)
Colors	16.7M Colors
Response Time	16ms Ton
Life Time (hours)	50.000
Protective Glass	3mm with black border

#### CONNECTIVITY

Analogue RGB Input	1xDB15
Digital Input	1xDVI-D
RS-232 Control	1xDB9
RS-485/422 Control	2xRJ45 (In/Out)

#### CONTROL

Remote Control	1xRS232, 1xRS485/422
Manual Control	1 Pushbuttons (Up/Down)

#### ELECTRICAL

Power Adaptor	90 - 264VAC to 12VDC 47 - 63Hz
Power Consumption	30W
Energy Management	VESA DPMS

#### MECHANICAL (SRET215S-10)

Screen (mm)	TBD
Under-table Housing (mm)	TBD
NET Weight (Kg)	TBD
Packaging dimensions (mm)	TBD
Gross Weight (Kg)	TBD

#### ENVIRONMENTAL CONDITIONS

Operation Temperature	0° to 50°
Storage Temperature	-20° to 60°
Operation Humidity (%)	5 to 90
Storage Humidity (%)	5 to 90

#### OTHERS

Certifications	CE, RoHS, BIS, EAC
Plug & Play	VESA DDC2Bi
Accessories	Mains Power Cord User Manual

Specifications subject to change without prior notice

# SRET215S-10

**SOLTEC**  
GENERAL DIMENSIONS

## RETRACTABLE MOTORIZED MONITOR

### RET M Line

#### CONSULTANTS & ARCHITECTS

Technical product description

Retractable Motorized 21.5" TFT Monitor with slim design of 20mm and automatic 20° tilt. Monitor housing made of anodized aluminium.

Built-in 3mm protective glass with black border serigraphy. The monitor has de minimal effect on boardroom table mechanization.

Native resolution Full HD 1920x1080. Two electrical engines, one for the lift system and the other one for the tilt adjustment. One pushbutton for the up/down lift system.

VGA and DVI inputs. 1xRS-232 serial control through DB9 connector and 1xRS-485/422 serial control through RJ45 connector in loop and addressing. External power supply.



